PolvOne

## MATERIAL SAFETY DATA SHEET AQUAMIX 1281

Version Number 1.0 Revision Date 11/08/2012 Page 1 of 7 Print Date 11/20/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AQUAMIX 1281
Product code	:	FO20030378
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Ziram	137-30-4	5 - 10
Sulfur	7704-34-9	10 - 30
Zinc oxide	1314-13-2	5 - 10

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This product has not been evaluated as a whole for health effects. Information provided on the health effects of this product is based on individual components. In addition, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Skin contact, Inhalation, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	:

PolyOne.

# MATERIAL SAFETY DATA SHEET **AQUAMIX 1281**

Version Number 1.0 Revision Date 11/08/2012 Page 2 of 7 Print Date 11/20/2012

Medical Conditions	: None known.
Aggravated by Exposure:	. Tone known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Never give anything by mouth to an unconscious person. Seek medical attention if necessary. Do not induce vomiting without medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>no data available</li> <li>Carbon dioxide (CO2), Water, Foam, Dry chemical.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.</li> <li>Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.



# MATERIAL SAFETY DATA SHEET **AQUAMIX 1281**

sion Number 1.0 ision Date 11/08/2012	Page 2 Print Date 11/20/
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitab containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.
Storage	: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. Airborne contaminant levels should be maintained below the occupational exposure guidelines.
Eye/Face Protection	: Safety glasses with side-shields Wear goggles or face shield during operations that present a splash potential.
Hand protection	: Impervious gloves such as rubber or PVC
Skin and body protection	: Long sleeved shirts and long pants are adequate for normal handling Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.
Engineering measures	: Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)	

PolyOne

# MATERIAL SAFETY DATA SHEET AQUAMIX 1281

Version Number 1.0 Revision Date 11/08/2012 Page 4 of 7 Print Date 11/20/2012

Components	Value	Exposure time	Exposure type	List:	
Zinc oxide	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH	
	10 mg/m3	Short Term Exposure Limit (STEL):	Respirable fraction.	ACGIH	
	5 mg/m3	Recommended exposure limit (REL):	Fume.	NIOSH	
	5 mg/m3	Recommended exposure limit (REL):	Dust.	NIOSH	
	15 mg/m3	Ceiling Limit Value and Time Period (if specified):	Dust.	NIOSH	
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	NIOSH	
	5 mg/m3	PEL:	Fume.	OSHA Z1	
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	5 mg/m3	Time Weighted Average (TWA):	Fume.	OSHA Z1A	
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A	
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A	
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	OSHA Z1A	
	5 mg/m3	Time Weighted Average (TWA):	Fume.	MX OEL	
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL	
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	MX OEL	
	9. PHYSIC	CAL AND CHEMICAL PRO	<b>PERTIES</b>		
Form	: liqui	d Evapo		wer than Buty etate	
Appearance	: liqui			determined	
Colour		PIGMENT Bulk d		applicable	
Ddour	: sligh		1	established	
			hereit Hereit		

: Not established : completely miscible

: not applicable

Melting point/range

Boiling Point:

Water solubility

# Bulk density: Not establishedVapour pressure: Not establishedVapour density: Heavier than air....: Not determined

#### **10. STABILITY AND REACTIVITY**

Stability	: The	product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will	not occur.
Conditions to avoid	: Extr	emes of temperature and direct sunlight. Keep from freezing.

## MATERIAL SAFETY DATA SHEET AQUAMIX 1281

#### Version Number 1.0 Revision Date 11/08/2012

Page 5 of 7 Print Date 11/20/2012

Incompatible Materials	:	Acids, metal salts, and solvents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
137-30-4	Ziram	Systemic effects	Liver, Kidney, reproductive
			system.
		Toxic	Refer to LC50 / LD50 Data on
			MSDS
7704-34-9	Sulfur	Irritant	Eyes, Skin, Respiratory
			system.
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
137-30-4	Ziram	LC50	81 mg/m3	rat
		Oral LD50	267 mg/kg	rat
		Dermal LD50	> 2 gm/kg	rabbit
1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		LC50		mouse
		Oral LD50	7,950 mg/kg	mouse

#### Additional Health Hazard Information:

Ziram 137-30-4 Highly toxic, irritant and a skin sensitizer. This material if ingested my cause an Antabuse response when alcohol is ingested. This Antabuse effect includes nausea, vomiting, abdominal cramps and/or flushing.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	no data available
Environmental Toxicity	:	no data available
Bioaccumulation Potential	:	no data available
Additional advice	:	no data available

#### **13. DISPOSAL CONSIDERATIONS**



# MATERIAL SAFETY DATA SHEET AQUAMIX 1281

	umber 1.0 Date 11/08/2012				Page Print Date 11/20	
Produ	ıct	generat classifi		as the responsition and disposal in		`he
Conta	aminated packaging	materia transpo	ing is preferred when p al has the responsibility prtation and disposal in rovincial and local regr	for proper wa accordance wi	ste classification,	
		14. TRA	NSPORT INFORMA	TION		
U.S. 1	DOT Classification	: Refer t	o specific regulation.			
ICAC	D/IATA	: Refer t	o specific regulation.			
IMO/	IMDG (maritime)	: Refer to	o specific regulation.			
		15 DECU				
		15. KEGU	LATORY INFORM	ATION		
US R	egulations:					
	OSHA Status	: Classif	ied as hazardous based	l on componen	ts.	
	TSCA Status		mponents of this produ Inventory.	ict are listed or	n or exempt from the	
US. E	EPA CERCLA Hazar	dous Substances (	40 CFR 302)			
	Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Pr	oduct	
	Ziram	137-30-4	010 lbs	134 LB		
SARA	California Proposit 65 A Title III Section 30					
		are identified und			plicable under this regu	ılatio
Che	emical Name		CAS-No.	% in Product	RQ for component	
SARA	A Title III Section 31	3 Toxic Chemical	s:			
			6/7			_
			6/7			

## MATERIAL SAFETY DATA SHEET AQUAMIX 1281

Version Number 1.0		
Revision Date 2	11/08/2012	

Page 7 of 7 Print Date 11/20/2012

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	1314-13-2	5.00 - 10.00
ZINC COMPOUNDS	137-30-4	5.00 - 10.00

Canadian Regulations:

National Pollutant Release Inventory (NPR	(I)
---	-----

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
2,6-Di-tert-butyl-p-cresol	128-37-0	0.10 - 1.00	
Zinc oxide	1314-13-2	5.00 - 10.00	
Ziram	137-30-4	5.00 - 10.00	

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.
1314-13-2
137-30-4

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.