PolvOne

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 1 of 8 Print Date 4/1/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-34711 ORANGE
Product code	:	FO20032711
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Aluminum oxide	1344-28-1	1 - 5
Antimony trioxide	1309-64-4	1 - 5
Barium	7440-39-3	1 - 5
Molybdate orange (Lead chromate pigment)	12656-85-8	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion Eyes Skin	 May be harmful if swallowed. May cause eye and skin irritation. Experience shows no unusual dermatitis hazard from routine handling.
SKIII	. Experience snows no unusual definations nazard from fourne nandring.

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 2 of 8 Print Date 4/1/2014

Medical Conditions : None known.				
Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
	5. FIREFIGHTING MEASURES			
Flash point	: no data available			
Flammable Limits				
Upper explosion limit	: no data available			
Lower explosion limit	: no data available			
Auto-ignition temperature	: Not applicable			
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.			
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive			
Procedures	pressure mode should be worn to prevent inhalation of airborne			
	contaminants.			
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.			
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.			
	7. HANDLING AND STORAGE			

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

rsion Number 1.0 vision Date 03/24/2014		Page 3 of Print Date 4/1/201
Handling	:	Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 4 of 8 Print Date 4/1/2014

Components	Value	Exposure time	Exposure type	List:
Aluminum oxide	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
Barium	0.5 mg/m3	Time Weighted Average (TWA):	as Ba	ACGIH
Molybdate orange (Lead chromate pigment)	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.005 mg/m3	Time Weighted Average (TWA):		OSHA
	0.0025 mg/m3	OSHA Action level:		OSHA
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH
	0.05 mg/m3	Time Weighted Average (TWA):		OSHA
	0.03 mg/m3	OSHA Action level:		OSHA
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	OSHA Z1A
	0.15 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Pb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility liquid
liquid, Viscous liquid dispersion
ORANGE
very faint
not applicable
not applicable
immiscible Evapouration rate Specific Gravity

pН

Bulk density:Vapour pressure:Vapour density:

:

:

Not applicable
Not determined
Heavier than air.
Not determined

Not established

Not determined

PolvOne

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 5 of 8 Print Date 4/1/2014

		10	. STABILITY AND REACTIVITY]
S	Stability	:	The product is stable if stored and handled as prescribed.	
ł	Hazardous Polymerization	:	Will not occur.	
(Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Ι	ncompatible Materials	:	Incompatible with strong acids and oxidizing agents.	
	Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1344-28-1	Aluminum oxide	Systemic effects	Eyes, Skin, Respiratory
			system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
7440-39-3	Barium	Irritant	Skin.
12656-85-8	Molybdate orange (Lead	Irritant	Eyes, Skin.
	chromate pigment)		
		Systemic effects	central nervous system (CNS),
			reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

Chemical Name	Route	Value	Species
Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat
Molybdate orange (Lead	Oral LD50	5,000 mg/kg	rat
	Antimony trioxide	Antimony trioxideOral LD50Molybdate orange (LeadOral LD50	Antimony trioxideOral LD50> 34,600 mg/kgMolybdate orange (LeadOral LD505,000 mg/kg

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no
12656-85-8	Molybdate orange (Lead	yes	1	no
	chromate pigment)			

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 6 of 8 Print Date 4/1/2014

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

 Not readily biodegradable. Environmental toxicity has not been established for this mixture as a whole. no data available no data available 13. DISPOSAL CONSIDERATIONS Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
 whole. no data available no data available 13. DISPOSAL CONSIDERATIONS Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
 no data available 13. DISPOSAL CONSIDERATIONS Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
 13. DISPOSAL CONSIDERATIONS : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
14. TRANSPORT INFORMATION
: Refer to specific regulation.
: Refer to specific regulation.
: Refer to specific regulation.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 **Revision Date**

ion Number 1.0 ision Date 03/24/2014			Page 7 of 8 Print Date <i>4/1/2014</i>			
1	5. REGULATORY INFO	RMATION				
US Regulations:						
OSHA Status :	Classified as hazardous b	ased on componen	ts.			
TSCA Status :	All components of this p TSCA Inventory.	roduct are listed or	n or exempt from the			
US. EPA CERCLA Hazardous Sul	bstances (40 CFR 302)					
not applicable						
California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.						
SARA Title III Section 302 Extrem	nely Hazardous Substance					
Unless specific chemicals are iden	tified under this section, this	s product is Not Ap	plicable under this regulation			
SARA Title III Section 313 Toxic Chemicals:						
Unless specific chemicals are iden	tified under this section, this					
Chemical Name		CAS-No.	Weight percent			
ALUMINUM OXIDE (FIBROU ANTIMONY COMPOUNDS	JS FORMS)	1344-28-1 1309-64-4	1.00 - 5.00 1.00 - 5.00			
CHROMIUM III COMPOUND	SCHROMIUM III	12656-85-8	1.00 - 5.00 30.00 - 60.00			
COMPOUNDSLEAD COMPO		12000 00 0	00.00			

Canadian Regulations:

National Pollutant Release Inventory (NPRI	()		
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Aluminum oxide	1344-28-1	1.00 - 5.00	
Antimony trioxide	1309-64-4	1.00 - 5.00	
Molybdate orange (Lead chromate pigment)	12656-85-8	30.00 - 60.00	

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-34711 ORANGE

Version Number 1.0 Revision Date 03/24/2014 Page 8 of 8 Print Date 4/1/2014

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1344-28-1
1309-64-4
7440-39-3
12656-85-8

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

China IECS : Listed	
Europe EINECS : Listed	
Japan ENCS : Not determined	ł
Korea KECI : Listed	
Philippines PICCS : Listed	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.