Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 1 of 18 Print Date 11/15/2016

SAFETY DATA SHEET

GeonTM MB2960 Black 50A Mold LC3

Section 1. Identification		
GHS product identifier	:	Geon™ MB2960 Black 50A Mold LC3
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20034503
Product type	:	liquid
<u>Relevant identified uses of the subs</u> Product use	stance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

GHS label elements



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1	Page 2 of 18
Revision Date 11/14/2016	Print Date 11/15/2016

Hazard pictograms	:	
Signal word Hazard statements	:	Warning Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	:	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20034503

CAS number/other identifiers

Ingredient name	%	CAS number
Calcium oxide	1 - 3	1305-78-8
Polypropylene glycol	1 - 3	25322-69-4
Carbon black	0.1 - 0.3	1333-86-4



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 3 of 18 Print Date 11/15/2016

Proprietary Hazardous Compounds	0.1 - 0.3	Not available.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Inhalation	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable
		for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

<u>vOne</u>.

Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 4 of 18 Print Date 11/15/2016

belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Inhalation Skin contact Ingestion	:	Causes serious eye irritation. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical atte	entio	n and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the	:	In a fire or if heated, a pressure increase will occur and the container



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1	Page 5 of 18
Revision Date 11/14/2016	Print Date 11/15/2016

chemical Hazardous thermal decomposition products	:	may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, so or air).	
Methods and materials for containn	nent a	nd cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-	
		5/18	

me

Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 6 of 18 Print Date 11/15/2016

combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name

Exposure limits



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016

Page 7 of 18 Print Date 11/15/2016

Calcium oxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 ACGIH TLV (1994-09-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3
Polypropylene glycol	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3 Form: Aerosol
Carbon black	OSHA PEL 1989 (1989-03-01)PEL: Permissible Exposure Level 3.5 mg/m3OSHA PEL (1993-06-30)PEL: Permissible Exposure Level 3.5 mg/m3NIOSH REL (1994-06-01)Time Weighted Average (TWA) 3.5 mg/m3Time Weighted Average (TWA)ACGIH TLV (2010-12-06)TLV-TWA: Threshold Limit Value - Time weighted average PEL:Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
Proprietary Hazardous Compounds	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations 7/18

<u>PolyOne</u>

Geon™ MB2960 Black 50A Mold LC3

Page 8 of 18
Print Date 11/15/2016

Eye/face protection		and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [liquid]
Color	:	BLACK
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.



Geon[™] MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 9 of 18 Print Date 11/15/2016

Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Polypropylene glycol				
	LD50 Oral	Rat	3,750 mg/kg	-
	LD50 Oral	Rat	15,000 mg/kg	-



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016

Page 10 of 18 Print Date 11/15/2016

	LD50 Oral	Rat	9,760 mg/kg	-
	LD50 Oral	Rat	10,334 mg/kg	-
	LD50 Oral	Rat	7,250 mg/kg	-
	LD50 Oral	Rat	2,150 mg/kg	-
	LD50 Oral	Rat	4,190 mg/kg	-
	LD50 Oral	Rat	5,840 mg/kg	-
	LD50 Oral	Rat	2,410 mg/kg	-
	LD50 Oral	Rat	5,840 mg/kg	-
	LD50 Oral	Rat	14,800 mg/kg	-
	LD50 Dermal	Rabbit	10,000 mg/kg	-
	LD50 Dermal	Rabbit	30,000 mg/kg	-
Carbon black	•	•	· · · ·	
	LD50 Oral	Rat	15,400 mg/kg	-
Proprietary Hazardous C	ompounds	•		•

Conclusion/Summary

Mixture.Not fully tested.

:

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Polypropylene glycol	Eyes - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				

Conclusion/Summary

Mixture.Not fully tested.

:

:

Skin Eyes

Mixture.Not fully tested.

)ne

Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 11 of 18 Print Date 11/15/2016

Respiratory	: N	: Mixture.Not fully tested.				
<u>Sensitization</u>						
Conclusion/Summary Skin Respiratory	Mixture.Not fully tested.Mixture.Not fully tested.					
Mutagenicity						
Conclusion/Summary	: N	/lixture.Not fully	tested.			
Carcinogenicity						
Conclusion/Summary Classification	: N	/lixture.Not fully	tested.			
Product/ingredient name	OSHA	IARC	NTP			
Carbon black		2B				
<u>Reproductive toxicity</u>						
Conclusion/Summary	: N	/lixture.Not fully	tested.			
<u>Teratogenicity</u>						
Conclusion/Summary	: N	/lixture.Not fully	tested.			
Specific target organ toxicity	(single exposu	ıre)				
Product/ingredient name	Category		ite of exposure	Target organs		
Calcium oxide	Category 3			Respiratory tract irritation		
Specific target organ toxicity	(repeated exp	oosure)				

Product/ingredient name Category Route of exposure Target organs Proprietary Hazardous Category 1 Category 1

Aspiration hazard

Not available.

Information on the likely routes of : Not available. exposure

Potential acute health effects



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 12 of 18 Print Date 11/15/2016

Eye contact Inhalation Skin contact Ingestion	:	Causes serious eye irritation. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.
2	, chemi	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following:
		pain or irritation
		watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following:
		irritation
		redness
Ingestion	:	No specific data.
Delayed and immediate effects and	<u>d also c</u>	chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects		Not available.
·		
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when
Concineranieity		subsequently exposed to very low levels. No known significant effects or critical hazards.
Carcinogenicity Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity		No known significant effects or critical hazards.
Developmental effects		No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		
Acute toxicity estimates		



Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016

Page 13 of 18 Print Date 11/15/2016

Route	ATE value
Oral	21,990.6 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Calcium oxide			
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
Polypropylene glycol			
	Acute LC50 1,700,000 µg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 650,000 µg/l Marine	Fish - Fish	96 h
	water		
Carbon black			
	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Conclusion/Summary	: Not available.	· •	•

Persistence and degradability

Conclusion/Summary

Not available.

:

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Calcium oxide		2.34	low
Polypropylene glycol	-0.68 - 0.01	-	low



Geon[™] MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016

Page 14 of 18 Print Date 11/15/2016

<u>Mobility in soil</u>

Soil/water partition coefficient:Not available.(KOC):No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Consult mode specific transport rules
IMO/IMDG (maritime)	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed
	14/18



Geon™ MB2960 Black 50A Mold LC3

Version Numbe	er 1.1
Revision Date	11/14/2016

Page 15 of 18 Print Date 11/15/2016

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Vinyl chloride monomer **Miscellaneous Zinc Compounds** Phenol 2-Ethylhexanoic acid zinc salt United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed Not listed •

Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

Clean Air Act Section 112(b)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312



Geon™ MB2960 Black 50A Mold LC3

:

Version Number 1.1 Revision Date 11/14/2016

Page 16 of 18 Print Date 11/15/2016

Classification

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Classification
Calcium oxide	1 - 3	AH
Polypropylene glycol	1 - 3	АН
Carbon black	0.1 - 0.3	СН
Proprietary Hazardous Compounds	0.1 - 0.3	F, AH, CH

SARA 313 Not applicable.

State regulations

Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
-		Carbon black
		Calcium oxide
		Ethene, chloro-, homopolymer
		Calcium carbonate
		Talc
Pennsylvania	:	The following components are listed:
·		Calcium oxide
		Calcium carbonate
		Talc
		Taic
		Carbon black
California Prop. 65		
	hemi	cal known to the State of California to cause cancer.
I		
United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory		All components are listed or exempted.
Canada myentory	•	The components are instea of exempted.

International regulations

Ine.

Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1	Page 17 of 18
Revision Date 11/14/2016	Print Date 11/15/2016

International lists	:	 Australia inventory (AICS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Malaysia Inventory (EHS Register): Not determined. EINECS: Not determined. China inventory (IECSC): Not determined. Korea inventory: Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Japan inventory: Not determined.
Chemical Weapons Convention	:	Not listed
List Schedule I Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule II Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule III Chemicals		

Section 16. Other information

History		
Date of printing	:	11/15/2016
Date of issue/Date of revision	:	11/14/2016
Date of previous issue	:	02/17/2015
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL $73/78$ = International Convention for the Prevention of Pollution
		From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
D. 4		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other

<u>vOne</u>

Geon™ MB2960 Black 50A Mold LC3

Version Number 1.1 Revision Date 11/14/2016 Page 18 of 18 Print Date 11/15/2016

materials or in any process, unless specified in the text.