

### Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 1 of 17 Print Date 10/30/2015

# SAFETY DATA SHEET

#### Geon<sup>TM</sup> V9444-80 Black Adhesive

## **Section 1. Identification**

**GHS product identifier** : Geon™ V9444-80 Black Adhesive

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20035073Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire,

exposure or accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

#### **GHS** label elements



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015

Page 2 of 17 Print Date 10/30/2015

Hazard pictograms :

❖

Signal word : Warning

**Hazard statements** : Causes serious eye irritation.

May cause an allergic skin reaction.

**Precautionary statements** 

**General** : Not applicable.

Prevention : Wear protective gloves. Wear eye or face protection. Avoid breathing

vapor. Wash hands thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace.

**Response** : IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Supplemental label elements** : None known. **Hazards not otherwise classified** : None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20035073

#### CAS number/other identifiers

Ingredient name	%	CAS number
Bisphenol A - Epichlorohydrin polymer	1 - 5	25068-38-6
Calcium oxide	1 - 5	1305-78-8
Carbon black	0.1 - 1	1333-86-4



### Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 3 of 17 Print Date 10/30/2015

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

**Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,



### Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 4 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact : May cause an allergic skin reaction.

Ingestion : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

**Unsuitable extinguishing media** : None known.



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 5 of 17 Print Date 10/30/2015

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container

may burst.

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 6 of 17 Print Date 10/30/2015

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

## Occupational exposure limits

Ingredient name	Exposure limits
	6/17



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 7 of 17 Print Date 10/30/2015

Calcium oxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 ACGIH TLV (1994-09-01)	
	TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3	
Carbon black	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction	

**Appropriate engineering controls** 

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

#### Skin protection



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 8 of 17 Print Date 10/30/2015

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

**Physical state** liquid [liquid] Color **BLACK** Odor Not available. **Odor threshold** Not available. Hq Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 9 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

**Kinematic:** Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

**Hazardous decomposition** : Under normal conditions of storage and use, hazardous decomposition

**products** products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
Bisphenol A - Epichlorohydri	Bisphenol A - Epichlorohydrin polymer					
	LD50 Oral	Rat	13,600 mg/kg	-		
	LD50 Oral	Rat	11,400 mg/kg	-		
	LD50 Oral	Rat	11,400 mg/kg	-		
	LD50 Oral	Rat	30,000 mg/kg	-		
	LD50 Oral	Rat	30,000 mg/kg	-		
	LD50 Oral	Rat	30,000 mg/kg	-		
	LD50 Oral	Rat	30,000 mg/kg	-		
	LD50 Oral	Rat	13,600 mg/kg	-		
Calcium oxide		<u> </u>	·	·		



Page 10 of 17

## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Print Date 10/30/2015 Revision Date 10/29/2015

Carbon black LD50 Oral 15,400 mg/kg Rat

**Conclusion/Summary** Mixture.Not fully tested.

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A -	Eyes - Mild	Rabbit			-
Epichlorohydrin polymer	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Skin - Severe	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				

**Conclusion/Summary** 

Skin Mixture.Not fully tested. **Eyes** Mixture.Not fully tested. Mixture.Not fully tested. Respiratory

**Sensitization** 

Conclusion/Summary

Skin Mixture.Not fully tested. Mixture.Not fully tested. Respiratory

**Mutagenicity** 

Conclusion/Summary Mixture.Not fully tested.

**Carcinogenicity** 

Conclusion/Summary Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Carbon black		2B	

**Reproductive toxicity** 

**Conclusion/Summary** Mixture.Not fully tested.



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 11 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

#### **Teratogenicity**

**Conclusion/Summary** : Mixture. Not fully tested.

**Specific target organ toxicity (single exposure)** 

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on the likely routes of** :

Not available.

exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contactMay cause an allergic skin reaction.IngestionIrritating to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

#### Long term exposure



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 12 of 17 Print Date 10/30/2015

Potential immediate effects: Not available.Potential delayed effects: Not available.

## Potential chronic health effects

**Conclusion/Summary**: Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### Numerical measures of toxicity

### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Calcium oxide				
	Chronic No-observable-effect- concentration 100 mg/l Fresh water	Fish - Fish	46 d	
	Chronic No-observable-effect- concentration 100 mg/l Fresh water	Fish - Fish	46 d	
	Chronic No-observable-effect- concentration 100 mg/l Fresh water	Fish - Fish	46 d	
	Chronic No-observable-effect- concentration 100 mg/l Fresh water	Fish - Fish	46 d	
	Chronic No-observable-effect- concentration 100 mg/l Fresh water	Fish - Fish	46 d	
Carbon black				
	Acute EC50 37.563 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h	
	Acute LC50 61.547 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h	
40/47				

12/17



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 13 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

**Conclusion/Summary** : Not available.

Persistence and degradability

**Conclusion/Summary** : Not available.

**Bioaccumulative potential** 

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A -	2.64 - 3.78	31.00	low
Epichlorohydrin polymer			
Calcium oxide		2.34	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## **Section 14. Transport information**



### Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 14 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Consult mode specific transport rules

IMO/IMDG (maritime) : Consult mode specific transport rules

## Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed
United States - TSCA 5(e) - Substances consent order: Not listed
United States - TSCA 6 - Proposed risk management: Not listed
United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
United States - TSCA 8(a) - Preliminary assessment report
(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed
United States - TSCA 8(d) - Health and safety studies: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 6 - Final risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed

United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Miscellaneous Zinc Compounds

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Not listed



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Page 15 of 17 Revision Date 10/29/2015 Print Date 10/30/2015

Clean Air Act Section 602 Class I : Not listed

**Substances** 

Clean Air Act Section 602 Class II : Not listed

**Substances** 

**DEA List I Chemicals (Precursor** : Not listed

Chemicals)

**DEA List II Chemicals (Essential**: Not listed

**Chemicals**)

### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Immediate (acute) health hazard

#### **Composition/information on ingredients**

Name	%	Classification
Bisphenol A - Epichlorohydrin polymer	1 - 5	АН
Calcium oxide	1 - 5	АН
Carbon black	0.1 - 1	СН

#### **SARA 313**

Not applicable.

**State regulations** 

Massachusetts : The following components are listed:

Calcium oxide

New York: None of the components are listed.New Jersey: The following components are listed:

Ethene, chloro-, homopolymer

Calcium oxide Carbon black

**Pennsylvania** : The following components are listed:

Calcium oxide

Carbon black

## California Prop. 65



### Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 16 of 17 Print Date 10/30/2015

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

International lists : Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): Not determined.

Malaysia Inventory (EHS Register): Not determined.

**EINECS:** Not determined.

**Japan inventory:** Not determined.

China inventory (IECSC): Not determined.

Korea inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

**Chemical Weapons Convention** 

List Schedule I Chemicals

**Chemical Weapons Convention** 

List Schedule II Chemicals

**Chemical Weapons Convention** 

List Schedule III Chemicals

Not listed

Not listed

Not listed

## **Section 16. Other information**

**History** 

Date of printing: 10/30/2015Date of issue/Date of revision: 10/29/2015Date of previous issue: 05/18/2015

Version : 1.1

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.



## Geon™ V9444-80 Black Adhesive

Version Number 1.1 Revision Date 10/29/2015 Page 17 of 17 Print Date 10/30/2015

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.