

Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018

Page 1 of 16 Print Date 12/06/2018

SAFETY DATA SHEET

GeonTM V1673 Lamination Adhesive

Section 1. Identification

GeonTM V1673 Lamination Adhesive **GHS** product identifier

Chemical name Mixture **CAS** number Mixture Other means of identification FO20035121 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Industrial applications. Plastics. Product use

Supplier's details POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

EYE IRRITATION - Category 2B

GHS label elements

Warning Signal word

Hazard statements Causes eye irritation.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 2 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

Precautionary statements

General : Not applicable.

Prevention: Wash hands thoroughly after handling.

Response: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If

eye irritation persists: Get medical attention.

Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20035121

CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	25 - 50	68515-48-0
C9-rich		
Quartz	0 - 0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 3 of 16 Print Date 12/06/2018

Continue to rinse for at least 10 minutes. If irritation persists, get

medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Skin contact

Eye contact : Causes eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 4 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the

chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for

fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel

> suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 5 of 16 Print Date 12/06/2018

For emergency responders

inadequate. Put on appropriate personal protective equipment.

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage,

Store in accordance with local regulations. Store in original container



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 6 of 16 Print Date 12/06/2018

including any incompatibilities

protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	None.
Quartz	OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO2+5) Form: Respirable TWA 10 MG /M3 / (%SiO2+2) Form: Respirable TWA 30 MG /M3 / (%SiO2+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m3 Form: Respirable dust

Appropriate engineering controls

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

necessary to reduce emissions to accept

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 7 of 16 Print Date 12/06/2018

remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color NO PIGMENT Not available. Odor **Odor threshold** Not available. Not available. Hq **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 8 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: Not available.Partition coefficient: n-: Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials: Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure
Remarks - Oral:	No applicable toxic	city data		
Remarks - Inhalation:	No applicable toxic	city data		



Geon™ V1673 Lamination Adhesive

 Version Number 1.3
 Page 9 of 16

 Revision Date 11/27/2018
 Print Date 12/06/2018

Remarks - Dermal:	No applicable toxic	city data		
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich				
	LD50 Oral	Rat	10,000 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxic	city data		

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingred	ient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedica	•	Eyes - Mild	Rabbit			-
alkyl esters, C9-		irritant				

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture. Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Quartz		1	Known to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary : Mixture. Not fully tested.

Teratogenicity

Conclusion/Summary: Mixture.Not fully tested.

Specific target organ toxicity (single exposure)



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 10 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Quartz	Category 1		

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 11 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Result	Species	Exposure	
No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich			
Remarks - Acute - Fish: No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
No applicable toxicity data			
	No applicable toxicity data di-C8-10-branched alkyl esters No applicable toxicity data No applicable toxicity data No applicable toxicity data No applicable toxicity data	No applicable toxicity data di-C8-10-branched alkyl esters, C9-rich No applicable toxicity data No applicable toxicity data	

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 12 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			

Mobility in soil

Soil/water partition coefficient

(KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

<u>United States - RCRA Acute hazardous waste "P" List:</u> Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 13 of 16 Print Date 12/06/2018

International Water IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a) 2 Final size if

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed (2-Methoxymethylethoxy)propanol

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Miscellaneous Zinc Compounds

Vinyl chloride monomer

Phenol

2-Ethylhexanoic acid zinc salt

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 14 of 16 Print Date 12/06/2018

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

: Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : EYE IRRITATION - Category 2B

Composition/information on ingredients

Name	%	Classification
1,2-Benzenedicarboxylic	>= 25 - <= 50	Immediate (acute) health hazard
acid, di-C8-10-branched		
alkyl esters, C9-rich		
Quartz	> 0 - <= 0.3	Delayed (chronic) health hazard

SARA 313

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Quartz

Calcium carbonate

Ethene, chloro-, homopolymer

Pennsylvania: The following components are listed:

Quartz

Calcium carbonate



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Page 15 of 16 Revision Date 11/27/2018 Print Date 12/06/2018

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable
		dosage level
Quartz	No.	No.
1,2-Benzenedicarboxylic acid, di-C8-10-	Yes.	No.
branched alkyl esters, C9-rich		

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : At least one component is not listed in DSL but all such components

are listed in NDSL.

International regulations

Inventory list

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components

are listed in NDSL.

China : Not determined.

Europe inventory : All components are listed or exempted.

Japan:Not determined.New Zealand:Not determined.Philippines:Not determined.Republic of Korea:Not determined.Taiwan:Not determined.Turkey:Not determined.

United States : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	1
Flammability		0
Physical hazards		0
•		

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4



Geon™ V1673 Lamination Adhesive

Version Number 1.3 Revision Date 11/27/2018 Page 16 of 16 Print Date 12/06/2018

representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 12/06/2018Date of issue/Date of revision: 11/27/2018Date of previous issue: 04/02/2018

Version : 1.3

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.