DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 1 of 18 Print Date 10/12/2022

SAFETY DATA SHEET

DNU V6031-81 GRANITE MOLDABLE

Section 1. Identification		
GHS product identifier	:	DNU V6031-81 GRANITE MOLDABLE
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20035400
Product type	:	liquid
Relevant identified uses of the subs	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2

GHS label elements

DNU V6031-81 GRANITE MOLDABLE



Version Number 1.7 Revision Date 10/10/2022

Page 2 of 18 Print Date 10/12/2022

Hazard pictograms	:	
Signal word Hazard statements	:	Warning Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Avoid breathing vapor. Wash thoroughly after handling.
Response	:	IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20035400

CAS number/other identifiers

Ingredient name	%	CAS number
2,4,4-Trimethyl-1,3-penytanediol diisobutyrate	>= 10 - <= 25	6846-50-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 1 - <= 3	68515-48-0

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 3 of 18 Print Date 10/12/2022

Titanium dioxide	>= 1 - <= 3	13463-67-7
Proprietary Hazardous Compounds	>= 1 - <= 2.9	Not available.
2-Hydroxy-4-n-octoxybenzophenone	> 0 - <= 0.3	1843-05-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 4 of 18 Print Date 10/12/2022

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Inhalation Skin contact Ingestion	 Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate medica	l attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth to mouth requesitation. Weak contaminated elething

See toxicological information (Section 11)

Section 5. Fire-fighting measures

give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 5 of 18 Print Date 10/12/2022

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters Special protective equipment for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for contain	Methods and materials for containment and cleaning up			
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal		
		E/19		

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 6 of 18 Print Date 10/12/2022

Large spill:Stop leak if without risk. Move containers from spill area. Approach
release from upwind. Prevent entry into sewers, water courses,
basements or confined areas. Wash spillages into an effluent treatment
plant or proceed as follows. Contain and collect spillage with non-
combustible, absorbent material e.g. sand, earth, vermiculite or
diatomaceous earth and place in container for disposal according to
local regulations (see Section 13). Dispose of via a licensed waste
disposal contractor. Contaminated absorbent material may pose the
same hazard as the spilled product. Note: see Section 1 for emergency
contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 7 of 18 Print Date 10/12/2022

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2,4,4-Trimethyl-1,3-penytanediol diisobutyrate	None.
1,2-Benzenedicarboxylic acid, di-C8-10- branched alkyl esters, C9-rich	None.
Proprietary Hazardous Compounds	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
2-Hydroxy-4-n-octoxybenzophenone	None.

Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 8 of 18 Print Date 10/12/2022

	higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting training and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [liquid]
Color	:	BLACK
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
-		

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 9 of 18 Print Date 10/12/2022

Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.
<u>Aerosol product</u> Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available. Not available.
8		
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition - Time equivalent Enclosed space ignition -	:	Not available.
Enclosed space ignition - Time equivalent Enclosed space ignition - Deflagration density	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-Benzenedicarboxylic acid, d	li-C8-10-branched al	lkyl esters, C9-rich		
	LD50 Oral	Rat	10,000 mg/kg	-
Titanium oxide (TiO2)				



DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022

Page 10 of 18 Print Date 10/12/2022

	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Methanone, [2-hydroxy-4-(octy	loxy)phenyl]phenyl-			
	LD50 Oral	Rat	10,000 mg/kg	-
	LD50 Dermal	Rabbit	10,000 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1- methylethyl)-1,3- propanediyl] ester	Skin - Mild irritant	Human	-	504 hrs	-
	Skin - Mild irritant	Guinea pig	-		-
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit	-		-

Conclusion/Summary		
Skin	: Mixture.	Not fully tested.
Eyes	: Mixture.	Not fully tested.
Respiratory	: Mixture.	Not fully tested.
Sensitization		
Conclusion/Summary		
Skin	: Mixture.	Not fully tested.
Respiratory	: Mixture.	Not fully tested.
Mutagenicity		
Conclusion/Summary	: Mixture.	Not fully tested.
Carcinogenicity		
Conclusion/Summary	: Mixture.N	Not fully tested.
Classification		

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 11 of 18 Print Date 10/12/2022

<u>Reproductive toxicity</u>		
Conclusion/Summary	:	Mixture.Not fully tested.
Teratogenicity		
Conclusion/Summary	:	Mixture.Not fully tested.
Specific target organ toxicity (single Not available.	<u>expo</u>	<u>sure)</u>
Specific target organ toxicity (repeat Not available.	ed er	<u>kposure)</u>
Aspiration hazard Not available.		
Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	:	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. No known significant effects or critical hazards.
Symptoms related to the physical, ch	emic	al and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation, watering, redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight,
Skin contact	:	increase in fetal deaths, skeletal malformations Adverse symptoms may include the following: irritation, redness,
Ingestion	:	reduced fetal weight, increase in fetal deaths, skeletal malformations Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations
Delayed and immediate effects and a	lso c	hronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 12 of 18 Print Date 10/12/2022

:	Not available. Not available.
:	Mixture.Not fully tested.
:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	Suspected of damaging the unborn child.
:	No known significant effects or critical hazards.
:	Suspected of damaging fertility.
	:

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
DNU V6031-81 GRANITE MOLDABLE	25,082.8 mg/kg	N/A	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10,000 mg/kg	N/A	N/A	N/A	N/A
Proprietary Hazardous Compounds	500 mg/kg	N/A	N/A	N/A	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	10,000 mg/kg	10,000 mg/kg	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022

Page 13 of 18 Print Date 10/12/2022

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
		dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		

Conclusion/Summary

Not available. :

Persistence and degradability

Conclusion/Summary Not available. :

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propanoic acid, 2-methyl-, 1,1'-[2,2- dimethyl-1-(1-methylethyl)-1,3-	-	5,340.00	high
propanediyl] ester			
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			
Methanone, [2-hydroxy-4-	6	99.00	low
(octyloxy)phenyl]phenyl-			

Mobility in soil

Soil/water partition coefficient : (KOC)

Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be



:

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 14 of 18 Print Date 10/12/2022

disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Listed 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not
	listed
	United States - TSCA 5(a)2 - Proposed significant new use rules:
	Listed 4-Nonylphenol, branched
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	14/19

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 15 of 18 Print Date 10/12/2022

		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Poly(dimethylsiloxane) (2-Methoxymethylethoxy)propanol 4-Nonylphenol, branched
		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed 2-Ethylhexanoic acid zinc salt Phenol Zinc pyrithione Vinyl chloride monomer
		United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 16 of 18 Print Date 10/12/2022

Composition/information on ingredients

Name	%	Classification
Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1-	>= 10 - <= 25	TOXIC TO REPRODUCTION - Category 2
methylethyl)-1,3- propanediyl] ester		
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 1 - <= 3	EYE IRRITATION - Category 2B
Proprietary Hazardous Compounds	>= 1 - <= 2.9	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY - oral - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1A
Titanium oxide (TiO2)	>= 1 - <= 3	CARCINOGENICITY - Category 2
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	> 0 - <= 0.3	SKIN SENSITIZATION - Category 1

Form R - Reporting requirements

Product name	CAS number	%
Proprietary Hazardous Compounds	-	>= 1 - <= 2.9

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

State regulations		
Massachusetts	:	The following components are listed: Proprietary Hazardous Compounds
New York	:	None of the components are listed.
New Jersey	:	The following components are listed: Ethene, chloro-, homopolymer Bis (2-ethylhexyl) adipate Proprietary Hazardous Compounds Titanium dioxide
Pennsylvania	:	The following components are listed: Bis (2-ethylhexyl) adipate

DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022



Page 17 of 18 Print Date 10/12/2022

Proprietary Hazardous Compounds

Titanium dioxide

California Prop. 65

WARNING: This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10-	Yes.	-
branched alkyl esters, C9-rich		
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations		
Inventory list		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	Not determined.
Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

-
0
0



DNU V6031-81 GRANITE MOLDABLE

Version Number 1.7 Revision Date 10/10/2022 Page 18 of 18 Print Date 10/12/2022

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Instory</u>		
Date of printing	:	10/12/2022
Date of issue/Date of revision	:	10/10/2022
Date of previous issue	:	05/04/2022
Version	:	1.7
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.