

Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 1 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

SAFETY DATA SHEET

GeonTM MM570 UV BLACK MAT PLASTISOL

Section 1. Identification

GHS product identifier : Geon™ MM570 UV BLACK MAT PLASTISOL

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20035561Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

GHS label elements



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 2 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Hazard pictograms :

Signal word : Warning

Hazard statements : May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Precautionary statements

: Not applicable.

Prevention : Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor.

Contaminated work clothing must not be allowed out of the

workplace.

Response : IF exposed or concerned: Get medical advice or attention. Wash

contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or

attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements Hazards not otherwise classified None known.
None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20035561

CAS number/other identifiers

Ingredient name	%	CAS number
2,4,4-Trimethyl-1,3-penytanediol diisobutyrate	>= 5 - <= 10	6846-50-0
Talc	>= 3 - <= 5	14807-96-6
Proprietary Hazardous Compounds	>= 0.3 - < 1	Not available.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 3 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Carbon black	> 0 - <= 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the
	upper and lower eyelids. Check for and remove any contact lenses.
	Continue to rinse for at least 10 minutes. Get medical attention

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 4 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Eye contact No known significant effects or critical hazards. No known significant effects or critical hazards. Inhalation

May cause an allergic skin reaction. Skin contact

Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact No specific data.

Inhalation Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Adverse symptoms may include the following: Skin contact

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

No specific treatment. **Specific treatments**

Protection of first-aiders No action shall be taken involving any personal risk or without

> suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the

chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

May emit Hydrogen Chloride (HCl). **Hazardous thermal**



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Page 5 of 17 Print Date 10/31/2023

decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Page 6 of 17 Print Date 10/31/2023

local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2,4,4-Trimethyl-1,3-penytanediol	None.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023

Page 7 of 17 Print Date 10/31/2023

diisobutyrate	
Talc	OSHA PEL Z3 (1997-09-03) TWA 20 million particles per 1 cubic foot Form: not/asb OSHA PEL Z3 (1997-09-03) STEL 1 fibers per cubic centimeter Form: not/asb TWA 0.1 fibers per cubic centimeter Form: con/asb STEL 1 fibers per cubic centimeter Form: con/asb ACGIH TLV (1996-05-18) TWA 2 mg/m3 Form: Respirable fraction ACGIH TLV (1998-09-01) TWA 0.1 fibers per cubic centimeter Form: respirable fibers: length> 5 .mu.m; length / diameter ratio (aspect) ³ 3: 1, determined by the membrane filter method at 400 - 450 x magnification (4mm objective) using illumination of phase contrast. NIOSH REL (1994-06-01) TWA 2 mg/m3 Form: Respirable fraction OSHA PEL 1989 (1989-03-01) TWA 2 mg/m3 Form: Respirable dust NIOSH REL (1994-06-01) TWA 6 mg/m3 Form: Total TWA 3 mg/m3 Form: Respirable fraction
Proprietary Hazardous Compounds Carbon black	None. OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction

Appropriate engineering controls If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. **Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Page 8 of 17 Print Date 10/31/2023

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : liquid [liquid]
Color : BLACK
Odor : Not available.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 9 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Odor threshold Not available. pН Not available. Not available. **Melting point Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: Not available.Partition coefficient: n-: Not applicable.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Aerosol product

Heat of combustion : Not available.

Ignition distance : Not available. **Enclosed space ignition - Time** : Not available.

equivalent

Enclosed space ignition - : Not available.

Deflagration density

Flame height : Not available.
Flame duration : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers



Page 10 of 17

Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Print Date 10/31/2023

during processing.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-

Conclusion/Summary Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1- methylethyl)-1,3- propanediyl] ester	Skin - Mild irritant	Human	-	504 hrs	-
	Skin - Mild irritant	Guinea pig	-		-
Talc	Skin - Mild irritant	Human	-	72 hrs	-

Conclusion/Summary

Mixture.Not fully tested. Skin Mixture.Not fully tested. **Eyes** Respiratory Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin Mixture.Not fully tested. Respiratory Mixture. Not fully tested.

Mutagenicity

Conclusion/Summary Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary Mixture.Not fully tested.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 11 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc	-	132B	-
Carbon black	-	2B	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of

exposure

Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Skin contact : Adverse symptoms may include the following: irritation, redness,

reduced fetal weight, increase in fetal deaths, skeletal malformations

Ingestion : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 12 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Potential immediate effects: Not available.Potential delayed effects: Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: Suspected of damaging the unborn child.Developmental effects: No known significant effects or critical hazards.

Fertility effects: Suspected of damaging fertility. Suspected of damaging fertility or the

unborn child.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Other information: This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Carbon black			
	Acute EC50 37.563 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		

Conclusion/Summary : Not available.

Persistence and degradability



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 13 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propanoic acid, 2-methyl-, 1,1'-[2,2-	-	5,340.00	high
dimethyl-1-(1-methylethyl)-1,3-			
propanediyl] ester			

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.



Page 14 of 17

Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Print Date 10/31/2023

International Air ICAO/IATA

: Consult mode specific transport rules

International Water IMO/IMDG

Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

United States - TSCA 5(a)2 - Proposed significant new use rules:

Listed 4-Nonylphenol, branched

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Octocrilene

(2-Methoxymethylethoxy)propanol

4-Nonylphenol, branched

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed 2-Ethylhexanoic acid zinc salt

Phenol

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Revision Date 10/30/2023 Page 15 of 17 Print Date 10/31/2023

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : SKIN SENSITIZATION - Category 1

CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

Name	%	Classification
Propanoic acid, 2-methyl-,	>= 5 - <= 10	TOXIC TO REPRODUCTION - Category 2
1,1'-[2,2-dimethyl-1-(1-		
methylethyl)-1,3-		
propanediyl] ester		
Talc	>= 3 - <= 5	CARCINOGENICITY - Category 2
Proprietary Hazardous	>= 0.3 - < 1	FLAMMABLE LIQUIDS - Category 4
Compounds		ACUTE TOXICITY - oral - Category 4
		SKIN CORROSION - Category 1B
		SERIOUS EYE DAMAGE - Category 1
		SKIN SENSITIZATION - Category 1A
Carbon black	> 0 - <= 0.3	CARCINOGENICITY - Category 2



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 16 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Not applicable.

State regulations

Massachusetts : The following components are listed:

Talc

New York: None of the components are listed.New Jersey: The following components are listed:

Ethene, chloro-, homopolymer

Talc

Paraffins, petroleum, normal C5-20

Carbon black

Pennsylvania : The following components are listed:

Talc

California Prop. 65

WARNING: This product can expose you to chemicals including Talc, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Talc	-	-
Carbon black	-	-

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia : Not determined.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic Union

Japan

Russian Federation inventory: Not determined.

Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand: Not determined.Philippines: Not determined.Republic of Korea: Not determined.

Taiwan : Not determined. Not determined.

Thailand : Not determined.
Turkey : Not determined.

United States : All components are active or exempted.

Viet Nam : Not determined.



Geon™ MM570 UV BLACK MAT PLASTISOL

Version Number 1.5 Page 17 of 17 Revision Date 10/30/2023 Print Date 10/31/2023

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 10/31/2023Date of issue/Date of revision: 10/30/2023Date of previous issue: 08/17/2020

Version : 1.5

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

 $MARPOL = International \ Convention \ for \ the \ Prevention \ of \ Pollution \ From$

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.