ne

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 1 of 16 Print Date 08/01/2017

SAFETY DATA SHEET

STAN-TONE EPX- EPOXY GRAY

Section 1. Identification	n	
GHS product identifier Chemical name CAS number Other means of identification Product type	::	STAN-TONE EPX- EPOXY GRAY Mixture Mixture FO20040661 liquid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION 1675 Navarre Road SW, Massillon, Ohio USA 44646
		1 330 837 8679
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B SKIN SENSITISATION - Category 1

GHS label elements



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 2 of 16 Print Date 08/01/2017

Hazard pictograms	:	
Signal word Hazard statements	:	Warning Causes skin and eye irritation. May cause an allergic skin reaction.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Wear protective gloves. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	:	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local,
Supplemental label elements		regional, national and international regulations. None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20040661

CAS number/other identifiers

Ingredient name	%	CAS number
Bisphenol A - Epichlorohydrin polymer	10 - 30	25068-38-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

<u>ColyUne</u>

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 3 of 16 Print Date 08/01/2017

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respirator arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	'y 1
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	:	Causes eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 4 of 16 Print Date 08/01/2017

:	Adverse symptoms may include the following: pain or irritation watering redness
:	No specific data.
:	Adverse symptoms may include the following: irritation redness
:	No specific data.
entio	n and special treatment needed, if necessary
:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
:	No specific treatment.
:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
	: : : : :

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

<u>vOne</u>

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 5 of 16 Print Date 08/01/2017

Special protective equipment for	:	Fire-fighters should wear appropriate protective equipment and self-
fire-fighters		contained breathing apparatus (SCBA) with a full face-piece operated
		in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containr	nent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1	Page 6 of 16
Revision Date 07/31/2017	Print Date 08/01/2017

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Bisphenol A - Epichlorohydrin polymer	
Appropriate engineering controls :	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls :	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	necessary to reduce emissions to acceptable levels.



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1	Page 7 of 16
Revision Date 07/31/2017	Print Date 08/01/2017

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state Color	iquid [Paste.] GREY
Odor	: Not available.
Odor threshold	: Not available.

Ine

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017

Page 8 of 16 Print Date 08/01/2017

		Not and lable
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017

Page 9 of 16 Print Date 08/01/2017

Acute toxicity

Result	Species	Dose	Exposure
n polymer			<u> </u>
LD50 Oral	Rat	13,600 mg/kg	-
LD50 Oral	Rat	11,400 mg/kg	-
LD50 Oral	Rat	11,400 mg/kg	-
LD50 Oral	Rat	30,000 mg/kg	-
LD50 Oral	Rat	30,000 mg/kg	-
LD50 Oral	Rat	30,000 mg/kg	-
LD50 Oral	Rat	30,000 mg/kg	-
LD50 Oral	Rat	13,600 mg/kg	-
	polymerLD50OralLD50OralLD50OralLD50OralLD50OralLD50OralLD50OralLD50OralLD50Oral	n polymerLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRatLD50 OralRat	n polymer Image: Constraint of the system LD50 Oral Rat 13,600 mg/kg LD50 Oral Rat 11,400 mg/kg LD50 Oral Rat 11,400 mg/kg LD50 Oral Rat 11,400 mg/kg LD50 Oral Rat 30,000 mg/kg

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A -	Eyes - Mild	Rabbit			-
Epichlorohydrin polymer	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Skin - Severe	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				

Skin	:	Mixture.Not fully tested.
Eyes	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.

Sensitization

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.
Mutagenicity		

Conclusion/Summary	:	Mixture.Not fully tested.

Carcinogenicity

<u>olyOne</u>.

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 10 of 16 Print Date 08/01/2017

Conclusion/Summary	:	Mixture.Not fully tested.	
<u>Reproductive toxicity</u>			
Conclusion/Summary	:	Mixture.Not fully tested.	
<u>Teratogenicity</u>			
Conclusion/Summary	:	Mixture.Not fully tested.	
Specific target organ toxicity (sing Not available.	le exp	<u>oosure)</u>	
Specific target organ toxicity (rependent) Not available.	eated	<u>exposure)</u>	
Aspiration hazard Not available.			
Information on likely routes of exposure	:	Not available.	
Potential acute health effects			
Eye contact Inhalation Skin contact Ingestion	:	Causes eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. No known significant effects or critical hazards.	
Symptoms related to the physical, o	chemi	cal and toxicological characteristics	
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering	
Inhalation Skin contact	:	redness No specific data. Adverse symptoms may include the following: irritation	
Ingestion	:	redness No specific data.	
Delayed and immediate effects as w	Delayed and immediate effects as well as chronic effects from short and long-term exposure		
Short term exposure			
Potential immediate effects	:	Not available.	
		10/16	

P<u>olyOne</u>

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 11 of 16 Print Date 08/01/2017

Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	44,884.1 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure		
STAN-TONE EPX- EPOXY GRAY					
Remarks - Acute - Aquatic	Dangerous f	the environment: May cause long terr	m adverse effects in the aquatic		
invertebrates.:	environmen				
Conclusion/Summary	:	: Dangerous for the environment: May cause long term adverse effects in the aquatic environment.			
Persistence and degradability					
Conclusion/Summary	:	Not available.			
Conclusion/Summary	:	angerous for the environment: May ca the aquatic environment.	ause long term adverse effects		
		11/16			

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 12 of 16 Print Date 08/01/2017

Bioaccumulative potential

Diouccumulative potential			
Product/ingredient name	LogPow	BCF	Potential
Bisphenol A -	2.64 - 3.78	31.00	low
Epichlorohydrin polymer			

Mobility in soil

Soil/water partition coefficient (KOC) Other adverse effects

Not available.

No known significant effects or critical hazards.

Section 13. Disposal considerations

:

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules

P<u>olyOne</u>

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 13 of 16 Print Date 08/01/2017

International Water IMO/IMDG : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a) 2 - Final significant new use rules: Not listed United States - TSCA 5(a) 2 - Proposed significant new use rules: Not listed United States - TSCA 5(c) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II	:	Not listed



STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 14 of 16 Print Date 08/01/2017

SubstancesDEA List I Chemicals (Precursor: Not listedChemicals)DEA List II Chemicals (Essential: Not listedChemicals): Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Classification
Bisphenol A - Epichlorohydrin	10 - 30	AH
polymer		

SARA 313

	Product name	CAS number	%
Form R - Reporting	Zinc sulfide	1314-98-3	30 - 60
requirements			
Supplier notification	Zinc sulfide	1314-98-3	30 - 60

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: The following components are listed:
	Zinc sulfide
Pennsylvania	: The following components are listed:
	Zinc sulfide

:

California Prop. 65

This PolyOne product does not contain any chemical known to the State of California to cause cancer, or birth defects or other reproductive harm, in concentrations that require a warning notice under California's Proposition 65. This statement relies in part on information provided by the buyer of this PolyOne product. PolyOne does not control or have complete knowledge of the end uses to which that buyer or any other entity in the chain of distribution and marketing may put this PolyOne product. Therefore, the buyer of this PolyOne product, each entity that uses this PolyOne product in formulating another product, and each entity in the chain of distribution and

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 15 of 16 Print Date 08/01/2017

e , i	the r	naterial in this PolyOne product must make its own decision as to giving
a Proposition 65 warning.		
United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :

Health	-	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History		
Date of printing	:	08/01/2017
Date of issue/Date of revision	:	07/31/2017
Date of previous issue	:	03/03/2017
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate
e e e e e e e e e e e e e e e e e e e		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals

STAN-TONE EPX- EPOXY GRAY

Version Number 1.1 Revision Date 07/31/2017 Page 16 of 16 Print Date 08/01/2017

IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.