## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 1 of 17 Print Date 03/16/2017

# SAFETY DATA SHEET

MB3051D Self-Adhering Plastisol

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification Product type	:	MB3051D Self-Adhering Plastisol Mixture Mixture FO20040801 liquid
	stance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012
Emergency telephone number (with hours of operation)	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

#### **GHS label elements**

# <u>PolyOne</u>.

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 2 of 17 Print Date 03/16/2017

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Causes serious eye damage. Causes skin irritation. May cause cancer.
Precautionary statements		
General Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response	:	IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements Hazards not otherwise classified	:	None known. None known.

## Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20040801

#### CAS number/other identifiers

Ingredient name	%	CAS number
Calcium oxide	10 - 30	1305-78-8
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10 - 30	68515-48-0



## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 3 of 17 Print Date 03/16/2017

Quartz	0.1 - 1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the

ne

## MB3051D Self-Adhering Plastisol

Version Number 1.0				
<b>Revision Date</b>	03/15/2017			

head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects

<ul><li>Causes serious eye damage.</li><li>No known significant effects or critical hazards.</li></ul>
Causes skin irritation.
No known significant effects or critical hazards.
• • • • • • • • • • • • • • • • • • • •
: Adverse symptoms may include the following: pain watering redness
: No specific data.
: Adverse symptoms may include the following: pain or irritation redness blistering may occur
<ul> <li>Adverse symptoms may include the following: stomach pains</li> </ul>
ention and special treatment needed, if necessary
: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
: No specific treatment.
: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

<u>vOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017

#### Page 5 of 17 Print Date 03/16/2017

## **Section 5. Firefighting measures**

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters Special protective equipment for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

<u>PolyOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017	Page 6 of 17 Print Date 03/16/2017
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate
Large spill	<ul> <li>waste disposal container. Dispose of via a licensed waste disposal contractor.</li> <li>Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-</li> </ul>
	combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

ne

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 7 of 17 Print Date 03/16/2017

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

OSHA - PEL Z3 (1997-09-03)         Time Weighted Average (TWA) Form: Respirable         Time Weighted Average (TWA) 10 mg/m3 Form: Total dust         NIOSH REL (1994-06-01)         Time Weighted Average (TWA) 0.05 mg/m3 Form: Total dust         NIOSH REL (1994-06-01)         Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable         ACGIH TLV (2005-12-09)         TLV-TWA: Threshold Limit Value - Time weighted average PE         Permissible Exposure Level 0.025 mg/m3 Form: Respirable         Calcium oxide         OSHA PEL 1989 (1989-03-01)         PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable         Calcium oxide         OSHA PEL (1993-06-30)         PEL: Permissible Exposure Level 5 mg/m3         OSHA PEL (1994-06-01)         Time Weighted Average (TWA) 2 mg/m3         ACGIH TLV (1994-06-01)         Time Weighted Average (TWA) 2 mg/m3         ACGIH TLV (1994-09-01)         TLV-TWA: Threshold Limit Value - Time weighted average PE         Permissible Exposure Level 2 mg/m3         1,2-Benzenedicarboxylic acid, di-C8-10-         branched alkyl esters, C9-rich         If user operations generate dust, fumes, gas, vapor or mist, use p         enclosures, local exhaust ventilation or other engineering control	Ingredient name	Exposure limits
PEL: Permissible Exposure Level 5 mg/m3         OSHA PEL (1993-06-30)         PEL: Permissible Exposure Level 5 mg/m3         NIOSH REL (1994-06-01)         Time Weighted Average (TWA) 2 mg/m3         ACGIH TLV (1994-09-01)         TLV-TWA: Threshold Limit Value - Time weighted average PE         Permissible Exposure Level 2 mg/m3         1,2-Benzenedicarboxylic acid, di-C8-10-         branched alkyl esters, C9-rich         If user operations generate dust, fumes, gas, vapor or mist, use p         enclosures, local exhaust ventilation or other engineering control	Quartz	OSHA PEL 1989 (1989-03-01) Calculated as Quartz PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust OSHA - PEL Z3 (1997-09-03) Time Weighted Average (TWA) Form: Respirable Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 30 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust
branched alkyl esters, C9-rich         Appropriate engineering controls       :         If user operations generate dust, fumes, gas, vapor or mist, use p enclosures, local exhaust ventilation or other engineering control	Calcium oxide	PEL: Permissible Exposure Level 5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL:
enclosures, local exhaust ventilation or other engineering contro		
recommended or statutory limits.		Emissions from ventilation or work process equipment should be

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

PolyOne.

## MB3051D Self-Adhering Plastisol

Version Number 1.0	Page 8 of 17
Revision Date 03/15/2017	Print Date 03/16/2017

. . . .

. . . . . .

. . . 1. 1

		necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used
		when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

**Appearance** 

P<u>olyOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 9 of 17 Print Date 03/16/2017

Physical state	:	liquid
Color	:	GREY
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.

## Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

<u>yOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017

Page 10 of 17 Print Date 03/16/2017

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-Benzenedicarboxylic acid,	di-C8-10-branched	alkyl esters, C9-rich		
	LD50 Oral	Rat	10,000 mg/kg	-
Conclusion/Summary	: Mixtu	re.Not fully tested.		

### **Conclusion/Summary**

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic	Eyes - Mild	Rabbit			-
acid, di-C8-10-branched	irritant				
alkyl esters, C9-rich					
Conclusion/Summary					
Skin	: N	lixture.Not fu	lly tested.		
Eyes		lixture.Not fu			
Respiratory	: N	lixture.Not fu	lly tested.		
<u>Sensitization</u>					
Conclusion/Summary					
Skin		lixture.Not fu			
Respiratory	: N	lixture.Not fu	lly tested.		
<u>Mutagenicity</u>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
<b>Carcinogenicity</b>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
<b><u>Classification</u></b>					
Product/ingredient	OSHA	IARC	NTP		
name					
Quartz		1	Known	to be a human carcin	ogen.
<b>Reproductive toxicity</b>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		

10/17

)n<u>e</u>.

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 11 of 17 Print Date 03/16/2017

#### **Teratogenicity**

**Conclusion/Summary** : Mixture.Not fully tested.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Quartz	Category 1		

<u>Aspiration hazard</u> Not available.		
Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye damage.
Inhalation		No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation.
Ingestion	:	No known significant effects or critical hazards.
<u>Symptoms related to the physical, ch</u> Eye contact	emi :	Adverse symptoms may include the following: pain
		watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains
Delayed and immediate effects as we	ll as	chronic effects from short and long-term exposure

#### Short term exposure

P<u>olyOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017

### Page 12 of 17 Print Date 03/16/2017

Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General Carcinogenicity	:	No known significant effects or critical hazards. May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity Teratogenicity Developmental effects Fertility effects	::	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	171,517.4 mg/kg

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Calcium oxide			
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	40/47		

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 13 of 17 Print Date 03/16/2017

**Conclusion/Summary** : Not available.

Persistence and degradability

Conclusion/Summary

Not available.

•

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential	
Calcium oxide		2.34	low	
1,2-Benzenedicarboxylic	8.8	3.00	low	
acid, di-C8-10-branched				
alkyl esters, C9-rich				

#### Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

:

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## **Section 14. Transport information**

<u>vOne</u>

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 14 of 17 Print Date 03/16/2017

U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Consult mode specific transport rules
IMO/IMDG (maritime)	:	Consult mode specific transport rules

## Section 15. Regulatory information

U.S. Federal regulations :	<b>United States - TSCA 12(b) - Chemical export notification:</b> None of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Listed 1,2- Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not listed
	United States - TSCA 5(a)2 - Proposed significant new use rules:
	Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Not listed
	United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Not listed
	United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed
	United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
	United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
	United States - Department of commerce - Precursor chemical: Not listed
	New Proced

Clean Air Act Section 112(b)

: Not listed

)n<u>e</u>.

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 15 of 17 Print Date 03/16/2017

Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
<b>DEA List I Chemicals (Precursor</b>	:	Not listed
Chemicals)		
<b>DEA List II Chemicals (Essential</b>	:	Not listed
Chemicals)		

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

#### SARA 311/312

Classification

Immediate (acute) health hazard Delayed (chronic) health hazard

#### **Composition/information on ingredients**

Name	%	Classification
Quartz	0.1 - 1	СН
Calcium oxide	10 - 30	АН
1,2-Benzenedicarboxylic acid, di- C8-10-branched alkyl esters, C9- rich	10 - 30	АН

### <u>SARA 313</u>

Not applicable.

#### **State regulations**

Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
-		Ethene, chloro-, homopolymer
		Graphite
		Quartz
		Calcium oxide
Pennsylvania	:	The following components are listed:
·		Quartz
		Calcium oxide

## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 16 of 17 Print Date 03/16/2017

#### <u>California Prop. 65</u> WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
International lists	:	<ul> <li>Australia inventory (AICS): All components are listed or exempted.</li> <li>Malaysia Inventory (EHS Register): Not determined.</li> <li>EINECS: All components are listed or exempted.</li> <li>Japan inventory: Not determined.</li> <li>China inventory (IECSC): All components are listed or exempted.</li> <li>Korea inventory: All components are listed or exempted.</li> <li>New Zealand Inventory of Chemicals (NZIoC): Not determined.</li> <li>Philippines inventory (PICCS): All components are listed or exempted.</li> <li>Taiwan Chemical Substances Inventory (TCSI): All components are listed or exempted.</li> </ul>
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention List Schedule II Chemicals	:	Not listed
Chemical Weapons Convention List Schedule III Chemicals	:	Not listed

## Section 16. Other information

#### Hazardous Material Information System (U.S.A.) :

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History

Date of printing	:	03/16/2017
Date of issue/Date of revision	:	03/15/2017



## MB3051D Self-Adhering Plastisol

Version Number 1.0 Revision Date 03/15/2017 Page 17 of 17 Print Date 03/16/2017

Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.