

LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 1 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

SAFETY DATA SHEET

LX-A-2052 NATURAL LATEX ADHESIVE

Section 1. Identification

GHS product identifier : LX-A-2052 NATURAL LATEX ADHESIVE

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20041159Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

1675 Navarre Road SW, Massillon,

Ohio USA 44646

1 330 837 8679

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

: CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2

GHS label elements



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 2 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Hazard pictograms

③

Signal word : Danger

Hazard statements : May cause cancer.

Suspected of damaging fertility or the unborn child.

Precautionary statements

General : Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves.

Wear eye or face protection. Wear protective clothing.

Response: IF exposed or concerned: Get medical attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements: None known. **Hazards not otherwise classified**: None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20041159

CAS number/other identifiers

Ingredient name	%	CAS number
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	0.3 - 1	68610-51-5
Ethyl alcohol	0 - 0.3	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 3 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 4 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO_2 .

None known.

Specific hazards arising from the

chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container

may burst.

Decomposition products may include the following materials:

carbon dioxide

carbon monoxide



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 5 of 18 Print Date 07/17/2020

nitrogen oxides sulfur oxides

Special protective actions for firefighters

for

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders

inadequate. Put on appropriate personal protective equipment.

if specialized clothing is required to deal with the spillage, take

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate

waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 6 of 18 Print Date 07/17/2020

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	None.
Ethyl alcohol	OSHA PEL 1989 (1989-03-01) TWA 1,900 mg/m3 1,000 ppm



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 7 of 18 Print Date 07/17/2020

OSHA PEL (1993-06-30) TWA 1,900 mg/m3 1,000 ppm NIOSH REL (1994-06-01) TWA 1,900 mg/m3 1,000 ppm ACGIH TLV (2008-11-24) STEL 1,000 ppm

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 8 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] NO PIGMENT Color Odor Not available. **Odor threshold** Not available. Hq Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available.

(flammable) limits

Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Aerosol product

Heat of combustion : Not available.



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 9 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Ignition distance Enclosed space ignition - Time

equivalent

Enclosed space ignition -

Deflagration density

Flame height

Not available.

Not available.

Not available.

Not available.

Flame duration Not available.

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

Stable under recommended storage and handling conditions (see **Chemical stability**

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid Keep away from extreme heat and oxidizing agents.

Incompatible materials Keep away from strong acids.

Oxidizer.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure	
Ethyl alcohol					
	LD50 Oral	Rat	7,000 mg/kg	-	
	LC50 Inhalation	Rat	124.7 Mg/l	4 h	
Remarks - Dermal: No applicable toxicity data					
Phenol, 4-methyl-, reaction pro	Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene				
	LD50 Oral	Rat	16,000 mg/kg	=	
Remarks - Inhalation:	No applicable toxicity data				
	LD50 Dermal	Rabbit	5,010 mg/kg	-	

Conclusion/Summary Mixture.Not fully tested.



LX-A-2052 NATURAL LATEX ADHESIVE

 Version Number 1.1
 Page 10 of 18

 Revision Date 07/16/2020
 Print Date 07/17/2020

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl alcohol	Eyes -	Rabbit			-
	Moderate				
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes -	Rabbit		0.001 hrs	-
	Moderate				
	irritant				
Phenol, 4-methyl-, reaction	Eyes - Mild	Rabbit			-
products with	irritant				
dicyclopentadiene and					
isobutylene					

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 11 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Skin contact: Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Ingestion : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.



LX-A-2052 NATURAL LATEX ADHESIVE

 Version Number 1.1
 Page 12 of 18

 Revision Date 07/16/2020
 Print Date 07/17/2020

Long term exposure

Potential immediate effects: Not available.Potential delayed effects: Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: Suspected of damaging the unborn child.Developmental effects: No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol			
	Acute LC50 0.042 Mg/l Fresh	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		
	Acute EC50 0.002 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute LC50 25.5 Mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute EC50 17.921 Mg/l Marine	Aquatic plants - Algae	96 h
	water		



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 13 of 18 Print Date 07/17/2020

Remarks - Acute - Aquatic	Acute			
plants:				
_	Acute NOEC 4.995 Mg/l Marine	Aquatic plants - Algae	96 h	
	water			
Remarks - Acute - Aquatic	Chronic			
plants:			_	
	Chronic NOEC 0.375 Mg/l Fresh	Fish - Fish	84 d	
	water			
Remarks - Chronic - Fish:	Chronic			
	Chronic NOEC 100 Mg/l Fresh	Aquatic invertebrates.	21 d	
	water	Daphnia		
Remarks - Chronic -	Chronic			
Aquatic invertebrates.:				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene				
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
LX-A-2052 NATURAL LATE	EX ADHESIVE			
Remarks - Acute - Aquatic	Dangerous for the environment: May cause long term adverse effects in the aquatic			
invertebrates.:	environment.			

Conclusion/Summary

Dangerous for the environment: May cause long term adverse effects

in the aquatic environment.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethyl alcohol	-0.35	-	low

Mobility in soil

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13/18



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 14 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR : Not regulated for transportation.

Ground/Air/Water

: Consult mode specific transport rules

International Water

International Air

IMO/IMDG

ICAO/IATA

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 15 of 18 Print Date 07/17/2020

United States - TSCA 5(a)2 - Final significant new use rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Glutaraldehyde

Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-,branched

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Zinc bis dibutyldithiocarbamate

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Not listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 16 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Classification : CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION - Fertility - Category 2 TOXIC TO REPRODUCTION - Unborn child - Category 2

Composition/information on ingredients

Name	%	Classification
Phenol, 4-methyl-, reaction	>= 0.3 - <= 1	TOXIC TO REPRODUCTION - Fertility - Category 2
products with		TOXIC TO REPRODUCTION - Unborn child - Category 2
dicyclopentadiene and		
isobutylene		
Ethyl alcohol	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 2
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		CARCINOGENICITY - Category 1A

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Ethyl alcohol

Pennsylvania : The following components are listed:

Ethyl alcohol

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : At least one component is not listed in DSL but all such components

are listed in NDSL.

International regulations

Inventory list

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components

are listed in NDSL.

China : Not determined.

16/18



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Page 17 of 18 Revision Date 07/16/2020 Print Date 07/17/2020

Europe inventory : Not determined.

Japan : Not determined.

New Zealand : Not determined.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : Not determined.

Turkey : Not determined.

United States : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	0
Flammability		0
Physical hazards		0
		•

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 07/17/2020Date of issue/Date of revision: 07/16/2020Date of previous issue: 05/16/2017

Version : 1.1

Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.



LX-A-2052 NATURAL LATEX ADHESIVE

Version Number 1.1 Revision Date 07/16/2020 Page 18 of 18 Print Date 07/17/2020

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.