

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

 Version Number 1.0
 Revision Date 05/01/2018

 Page 1 of 20
 Print Date 05/02/2018

SAFETY DATA SHEET

Geon™ DB5447 GRAY FAST FUSE SELF BOND
Section 1. Identification

GHS product identifier : Geon™ DB5447 GRAY FAST FUSE SELF BOND
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO20043033
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012

 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN IRRITATION - Category 2
 SERIOUS EYE DAMAGE - Category 1
 CARCINOGENICITY - Category 1A

GHS label elements

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 2 of 20
Print Date 05/02/2018

Hazard pictograms


Signal word : Danger
Hazard statements : Causes serious eye damage.
Causes skin irritation.
May cause cancer.

Precautionary statements

General : Not applicable.
Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage : Store locked up.
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements : None known.
Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Chemical name : Mixture
Other means of identification : FO20043033

CAS number/other identifiers

| Ingredient name | % | CAS number |
|------------------------------|---------|------------|
| Calcium oxide | 10 - 20 | 1305-78-8 |
| Magnesium aluminium silicate | 1 - 3 | 12174-11-7 |

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 3 of 20
Print Date 05/02/2018

| | | |
|------------------|---------|------------|
| | | |
| Quartz | 0.3 - 1 | 14808-60-7 |
| Titanium dioxide | 0.3 - 1 | 13463-67-7 |
| Carbon black | 0 - 0.3 | 1333-86-4 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician.

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 4 of 20
Print Date 05/02/2018

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed
Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 5 of 20
Print Date 05/02/2018

apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** : May emit Hydrogen Chloride (HCl).
Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 6 of 20
Print Date 05/02/2018

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- | | | |
|--------------------|---|---|
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

- | | | |
|---|---|--|
| Protective measures | : | Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and |

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

 Version Number 1.0
 Revision Date 05/01/2018

 Page 7 of 20
 Print Date 05/02/2018

drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection
Control parameters
Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------------|---|
| Calcium oxide | OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 5 mg/m ³ OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 5 mg/m ³ NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m ³ ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m ³ |
| Magnesium aluminium silicate | |
| Titanium dioxide | OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m ³ Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m ³ Form: Total dust NIOSH REL (1994-06-01) ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m ³ |
| Quartz | OSHA PEL 1989 (1989-03-01) Calculated as Quartz PEL: Permissible Exposure Level 0.1 mg/m ³ Form: Respirable dust OSHA PEL Z3 (1997-09-03) Time Weighted Average (TWA) Form: Respirable Time Weighted Average (TWA) 10 mg/m³ Form: Respirable Time Weighted Average (TWA) 30 mg/m³ Form: Total dust NIOSH REL (1994-06-01) |

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 8 of 20
Print Date 05/02/2018

| | |
|--------------|---|
| | <p>Time Weighted Average (TWA) 0.05 mg/m³ Form: Respirable dust ACGIH TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m³ Form: Respirable fraction OSHA PEL (2016-06-23) PEL: Permissible Exposure Level 0.05 mg/m³ Form: Respirable dust</p> |
| Carbon black | <p>OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m³ OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m³ NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m³ Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m³ Form: Inhalable fraction</p> |

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 9 of 20
Print Date 05/02/2018

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : liquid [liquid]
Color : GREY
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : Not available.
Flash point : Not available.
Burning time : Not available.
Burning rate : Not available.
Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : **Lower:** Not available.
Upper: Not available.
Vapor pressure : Not available.
Vapor density : Not available.
Relative density : Not available.
Solubility : Not available.
Solubility in water : Not available.

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

 Version Number 1.0
 Revision Date 05/01/2018

 Page 10 of 20
 Print Date 05/02/2018

Partition coefficient: n-octanol/water : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
SADT : Not available.
Viscosity : **Dynamic:** Not available.
Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : Keep away from extreme heat and oxidizing agents.
Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects
Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------|-----------------------------|------------|--------------|----------|
| Carbon black | | | | |
| | LD50 Oral | Rat | 15,400 mg/kg | - |
| Remarks - Inhalation: | No applicable toxicity data | | | |
| Remarks - Dermal: | No applicable toxicity data | | | |
| Quartz | | | | |
| Remarks - Oral: | No applicable toxicity data | | | |
| Remarks - Inhalation: | No applicable toxicity data | | | |
| Remarks - Dermal: | No applicable toxicity data | | | |
| Titanium dioxide | | | | |
| Remarks - Oral: | No applicable toxicity data | | | |
| | LC50 Inhalation | Rat - Male | 6.82 Mg/l | 4 h |

SAFETY DATA SHEET

Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 11 of 20
Print Date 05/02/2018

| | | | | |
|------------------------------|-----------------------------|--------|---------------|---|
| | LD50 Dermal | Rabbit | > 5,000 mg/kg | - |
| Magnesium aluminium silicate | | | | |
| Remarks - Oral: | No applicable toxicity data | | | |
| Remarks - Inhalation: | No applicable toxicity data | | | |
| Remarks - Dermal: | No applicable toxicity data | | | |
| Calcium oxide | | | | |
| Remarks - Oral: | No applicable toxicity data | | | |
| Remarks - Inhalation: | No applicable toxicity data | | | |
| Remarks - Dermal: | No applicable toxicity data | | | |

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|----------------------|---------|-------|----------|-------------|
| Titanium dioxide | Skin - Mild irritant | Human | | 72 hrs | - |

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization
Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity
Conclusion/Summary

: Mixture.Not fully tested.

Carcinogenicity
Conclusion/Summary

: Mixture.Not fully tested.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|------------------------------|------|-------|-----|
| Carbon black | | 2B | |
| Quartz | | 1 | |
| Titanium dioxide | | 2B | |
| Magnesium aluminium silicate | | 2B, 3 | |

Reproductive toxicity

SAFETY DATA SHEET

Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 12 of 20
Print Date 05/02/2018

Conclusion/Summary : Mixture. Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture. Not fully tested.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| Calcium oxide | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| Quartz | Category 1 | | |

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain
 watering
 redness
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
Ingestion : Adverse symptoms may include the following:
 stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 13 of 20
Print Date 05/02/2018

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General : No known significant effects or critical hazards.
Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity
Acute toxicity estimates

Not available.

Section 12. Ecological information
Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|------------------------------------|-----------------------------------|----------|
| Carbon black | | | |
| Remarks - Acute - Fish: | No applicable toxicity data | | |
| | Acute EC50 37.563 Mg/l Fresh water | Aquatic invertebrates. Daphnia | 48 h |
| Remarks - Acute - Aquatic invertebrates.: | Acute | | |
| Remarks - Acute - Aquatic plants: | No applicable toxicity data | | |
| Remarks - Chronic - Fish: | No applicable toxicity data | | |

SAFETY DATA SHEET

Geon™ DB5447 GRAY FAST FUSE SELF BOND

 Version Number 1.0
 Revision Date 05/01/2018

 Page 14 of 20
 Print Date 05/02/2018

| | | | |
|--|--------------------------------------|------------------------------------|------|
| Remarks - Chronic - Aquatic invertebrates.: | No applicable toxicity data | | |
| Quartz | | | |
| Remarks - Acute - Fish: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic invertebrates.: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic plants: | No applicable toxicity data | | |
| Remarks - Chronic - Fish: | No applicable toxicity data | | |
| Remarks - Chronic - Aquatic invertebrates.: | No applicable toxicity data | | |
| Titanium dioxide | | | |
| | Acute LC50 > 1,000 Mg/l Marine water | Fish - Fish | 96 h |
| Remarks - Acute - Fish: | Acute | | |
| | Acute LC50 3 Mg/l Fresh water | Aquatic invertebrates. Crustaceans | 48 h |
| Remarks - Acute - Aquatic invertebrates.: | Acute | | |
| | Acute LC50 6.5 Mg/l Fresh water | Aquatic invertebrates. Daphnia | 48 h |
| Remarks - Acute - Aquatic invertebrates.: | Acute | | |
| Remarks - Acute - Aquatic plants: | No applicable toxicity data | | |
| Remarks - Chronic - Fish: | No applicable toxicity data | | |
| Remarks - Chronic - Aquatic invertebrates.: | No applicable toxicity data | | |
| Magnesium aluminium silicate | | | |
| Remarks - Acute - Fish: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic invertebrates.: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic plants: | No applicable toxicity data | | |
| Remarks - Chronic - Fish: | No applicable toxicity data | | |
| Remarks - Chronic - Aquatic invertebrates.: | No applicable toxicity data | | |
| Calcium oxide | | | |
| Remarks - Acute - Fish: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic invertebrates.: | No applicable toxicity data | | |
| Remarks - Acute - Aquatic plants: | No applicable toxicity data | | |
| | Chronic NOEC 100 Mg/l Fresh | Fish - Fish | 46 d |

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 15 of 20
Print Date 05/02/2018

| | | | |
|--|-----------------------------|--|--|
| | water | | |
| Remarks - Chronic - Fish: | Chronic | | |
| Remarks - Chronic - Aquatic invertebrates.: | No applicable toxicity data | | |

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|------|-----------|
| Calcium oxide | - | 2.34 | low |

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 16 of 20
Print Date 05/02/2018

Section 14. Transport information

- U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.
- International Air ICAO/IATA : Consult mode specific transport rules
- International Water IMO/IMDG : Consult mode specific transport rules

Section 15. Regulatory information

- U.S. Federal regulations :
- United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.
 - United States - TSCA 4(a) - Final Test Rules:** Not listed
 - United States - TSCA 4(a) - ITC Priority list:** Not listed
 - United States - TSCA 4(a) - Proposed test rules:** Not listed
 - United States - TSCA 4(f) - Priority risk review:** Not listed
 - United States - TSCA 5(a)2 - Final significant new use rules:** Not listed
 - United States - TSCA 5(a)2 - Proposed significant new use rules:** Not listed
 - United States - TSCA 5(e) - Substances consent order:** Not listed
 - United States - TSCA 6 - Final risk management:** Not listed
 - United States - TSCA 6 - Proposed risk management:** Not listed
 - United States - TSCA 8(a) - Chemical risk rules:** Not listed
 - United States - TSCA 8(a) - Dioxin/Furane precursor:** Not listed
 - United States - TSCA 8(a) - Chemical Data Reporting (CDR):** Not determined
 - United States - TSCA 8(a) - Preliminary assessment report (PAIR):** Not listed
 - United States - TSCA 8(c) - Significant adverse reaction (SAR):** Not listed
 - United States - TSCA 8(d) - Health and safety studies:** Not listed
 - United States - EPA Clean water act (CWA) section 307 - Priority pollutants:** Listed Phenol
Vinyl chloride monomer
 - United States - EPA Clean water act (CWA) section 311 - Hazardous substances:** Listed

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 17 of 20
Print Date 05/02/2018

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) : Listed
Hazardous Air Pollutants (HAPs)
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Immediate (acute) health hazard
Delayed (chronic) health hazard

Composition/information on ingredients

| Name | % | Classification |
|------------------------------|---------|----------------|
| Carbon black | 0 - 0.3 | CH |
| Quartz | 0.3 - 1 | CH |
| Titanium dioxide | 0.3 - 1 | CH |
| Magnesium aluminium silicate | 1 - 3 | CH |
| Calcium oxide | 10 - 20 | AH |

SARA 313

Not applicable.

State regulations

Massachusetts : None of the components are listed.

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 18 of 20
Print Date 05/02/2018

- New York** : None of the components are listed.
New Jersey : The following components are listed:
 Calcium oxide
 Titanium dioxide
 Quartz
 Carbon black
 Calcium carbonate
 Ethene, chloro-, homopolymer
- Pennsylvania** : The following components are listed:
 Calcium oxide

 Titanium dioxide

 Quartz

 Carbon black

 Calcium carbonate

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

- United States inventory (TSCA 8b)** : All components are listed or exempted.
- Canada inventory** : At least one component is not listed in DSL but all such components are listed in NDSL.

International regulations
Inventory list

- Australia** : Not determined.
Canada : At least one component is not listed in DSL but all such components are listed in NDSL.
China : All components are listed or exempted.
Europe inventory : Not determined.
Japan : Not determined.
New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : Not determined.
Turkey : Not determined.
United States : All components are listed or exempted.

SAFETY DATA SHEET


Geon™ DB5447 GRAY FAST FUSE SELF BOND

 Version Number 1.0
 Revision Date 05/01/2018

 Page 19 of 20
 Print Date 05/02/2018

Section 16. Other information
Hazardous Material Information System (U.S.A.)

| | | |
|-------------------------|---|---|
| Health | * | 3 |
| Flammability | | 0 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing : 05/02/2018
Date of issue/Date of revision : 05/01/2018
Date of previous issue : 00/00/0000
Version : 1.0

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET



Geon™ DB5447 GRAY FAST FUSE SELF BOND

Version Number 1.0
Revision Date 05/01/2018

Page 20 of 20
Print Date 05/02/2018