

# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 1 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

# SAFETY DATA SHEET

CORETM SK461 (SB-BO-P)

# **Section 1. Identification**

**GHS product identifier** : CORE<sup>TM</sup> SK461 (SB-BO-P)

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20051048Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation)

ther : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2

#### **GHS** label elements



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 2 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

Hazard pictograms :



Signal word : Warning

**Hazard statements**: Flammable liquid and vapor.

Causes eye irritation.

Suspected of causing cancer.

**Precautionary statements** 

Not applicable.

**Prevention** : Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Wash thoroughly after

handling.

**Response**: IF exposed or concerned: Get medical advice or attention. IF ON

SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements

Hazards not otherwise classified : None known.

Not available.

None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture Chemical name : Mixture Other means of identification : FO20051048

#### **CAS** number/other identifiers

Ingredient name	%	CAS number
Solvent naphtha, petroleum, light arom.	>= 10 - <= 25	64742-95-6



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 3 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	95-63-6
Cumene	> 0 - <= 0.3	98-82-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the
	upper and lower eyelids. Check for and remove any contact lenses.
	Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

**Ingestion** : Wash out mouth with water. Remove dentures if any. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024

Page 4 of 18 Print Date 10/08/2024

Eye contact Causes eye irritation.

No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards. Skin contact **Ingestion** No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Adverse symptoms may include the following: Eye contact

> irritation watering redness

No specific data. Inhalation No specific data. Skin contact No specific data. **Ingestion** 

#### Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

**Specific treatments** No specific treatment.

**Protection of first-aiders** No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur

and the container may burst, with the risk of a subsequent explosion.

**Hazardous thermal** May emit Hydrogen Chloride (HCl). decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training. Move containers from fire



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 5 of 18 Print Date 10/08/2024

area if this can be done without risk. Use water spray to keep fireexposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

**For emergency responders**: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-

proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal

container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from

upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 6 of 18 Print Date 10/08/2024

# Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Solvent naphtha, petroleum, light arom.	None.



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 7 of 18 Print Date 10/08/2024

Benzene, 1,2,4-trimethyl-	NIOSH REL (1994-06-01) TWA 125 mg/m3 25 ppm OSHA PEL 1989 (1989-03-01) TWA 125 mg/m3 25 ppm ACGIH TLV (1994-09-01) TWA 123 mg/m3 25 ppm
Cumene	ACGIH TLV (2021-01-07) TWA 5 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 245 mg/m3 50 ppm

**Appropriate engineering controls** 

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

#### **Skin protection**



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 8 of 18 Print Date 10/08/2024

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing

should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

liquid [liquid] Physical state **ORANGE** Color Odor Not available. **Odor threshold** Not available. рH Not available. **Melting point** Not available. **Boiling point** Not available. Flash point 115 °F (46 °C)

Burning time: Not available.Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 9 of 18 Print Date 10/08/2024 Revision Date 10/07/2024

**Solubility** Not available. Solubility in water Not available. Partition coefficient: n-Not applicable.

octanol/water

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **SADT** 

Viscosity **Dynamic:** Not available.

Kinematic: Not available.

# Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

Stable under recommended storage and handling conditions (see **Chemical stability** 

Section 7).

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

Avoid contact with acetal homopolymers and acetyl homopolymers **Incompatible materials** 

during processing.

Reactive or incompatible with the following materials:

oxidizing materials

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

# Section 11. Toxicological information

#### **Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Solvent naphtha (petroleum), light arom.						
	LD50 Oral	Rat	8,400 mg/kg	-		
Benzene, 1,2,4-trimethyl-						
	LD50 Oral	Rat	5,000 mg/kg	-		
	LC50 Inhalation	Rat	18 Mg/l	4 h		
	Vapor					
Benzene, (1-methylethyl)-						
	LD50 Oral	Rat	1,400 mg/kg	-		
	LC50 Inhalation	Rat	39 Mg/l	4 h		
	Vapor					



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 10 of 18 Print Date 10/08/2024

**Conclusion/Summary** : Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum),	Eyes - Mild irritant	Rabbit	-	24 hrs	-
light arom.					
Benzene, (1-methylethyl)-	Eyes - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Eyes - Mild irritant	Rabbit	-		-

**Conclusion/Summary** 

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

**Conclusion/Summary** 

SkinMixture.Not fully tested.RespiratoryMixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Carcinogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Benzene, (1-methylethyl)-	-	2B	Reasonably anticipated to be a human carcinogen.

#### **Reproductive toxicity**

**Conclusion/Summary**: Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

#### **Specific target organ toxicity (single exposure)**

Not available.



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 11 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

Information on the likely routes of

exposure

Not available.

#### Potential acute health effects

**Eye contact** : Causes eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following: irritation, watering,

redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate effects : Not available.
Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

#### Potential chronic health effects

**Conclusion/Summary** : Mixture.Not fully tested.

**General**: No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

**Mutagenicity**: No known significant effects or critical hazards.

11/18



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 12 of 18 Print Date 10/08/2024

**Teratogenicity** : Not available. **Developmental effects** : Not available.

Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE™ SK461 (SB-BO-P)	85660.4 mg/kg	N/A	N/A	308.4 Mg/l	N/A
Solvent naphtha (petroleum), light arom.	8400 mg/kg	N/A	N/A	N/A	N/A
Benzene, 1,2,4-trimethyl-	5000 mg/kg	N/A	N/A	18 Mg/l	N/A
Benzene, (1-methylethyl)-	1400 mg/kg	N/A	N/A	39 Mg/l	N/A

Other information : This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Benzene, 1,2,4-trimethyl-			
	Acute LC50 7.72 Mg/l Fresh water	Fish - Pimephales promelas	96 h
	Acute LC50 4.91 Mg/l Marine water	Crustaceans - Elasmopus pectenicrus	48 h
Benzene, (1-methylethyl)-			
	Acute LC50 0.0027 Mg/l Fresh water	Fish - Oncorhynchus mykiss	96 h
	Acute EC50 7.4 Mg/l Marine water	Crustaceans - Artemia sp.	48 h
	Acute EC50 10.6 Mg/l Fresh water	Daphnia - Daphnia magna	48 h

**Conclusion/Summary** : Not available.



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 13 of 18 Print Date 10/08/2024

#### Persistence and degradability

Conclusion/Summary : Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Solvent naphtha (petroleum), light	-	10.00 - 2,500.00	high
arom.			
Benzene, 1,2,4-trimethyl-	3.63	243.00	low
Benzene, (1-methylethyl)-	3.55	35.48	low

#### Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

# **Section 13. Disposal considerations**

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024 Page 14 of 18 Print Date 10/08/2024

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : In accordance with 49CFR 173.150(f)(1) and (2), non-bulk quantities of this material may be shipped as non-regulated for USA domestic

highway transport only.

International Air ICAO/IATA

: UN1993, Flammable liquid, n.o.s. (Petroleum distillates), 3, PGIII

International Water

IMO/IMDG

UN1993, Flammable liquid, n.o.s. (Petroleum distillates), 3, PGIII

# Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Miscellaneous Zinc Compounds

Ethyl benzene

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024

Page 15 of 18 Print Date 10/08/2024

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

**Chemicals**)

**DEA List II Chemicals (Essential** 

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

als)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3

EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2

#### **Composition/information on ingredients**

Name	%	Classification
Solvent naphtha (petroleum), light arom.	>= 10 - <= 25	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B
<i>4</i>		ASPIRATION HAZARD - Category 1
Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4
Benzene, (1-methylethyl)-	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2

#### **SARA 313**



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 16 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

#### Form R - Reporting requirements

Product name	CAS number	<b>%</b>
Benzene, 1,2,4-trimethyl-	95-63-6	>= 3 - < 7
Cumene	98-82-8	>= 0.1 - < 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts : The following components are listed:

Benzene, 1,2,4-trimethyl-

New York : None of the components are listed.

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

Solvent naphtha, petroleum, light arom.

Benzene, 1,2,4-trimethyl-

**Pennsylvania** : The following components are listed:

Benzene, 1,2,4-trimethyl-

#### California Prop. 65

**WARNING:** This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Cumene	-	-

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : At least one component is not listed in DSL but all such components

are listed in NDSL.

**International regulations** 

**Inventory list** 

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components

are listed in NDSL.

China : Not determined.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan inventory (CSCL): Not determined.

16/18



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Page 17 of 18 Revision Date 10/07/2024 Print Date 10/08/2024

Japan inventory (ISHL): Not determined.

New ZealandNot determined.PhilippinesNot determined.Republic of KoreaNot determined.TaiwanNot determined.ThailandNot determined.TurkeyNot determined.

**United States** : All components are active or exempted.

Viet Nam : Not determined.

### Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**

Health	*	1
Flammability		2
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### History

Date of printing: 10/08/2024Date of issue/Date of revision: 10/07/2024Date of previous issue: 00/00/0000

Version : 1.0

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader



# CORE™ SK461 (SB-BO-P)

Version Number 1.0 Revision Date 10/07/2024

Page 18 of 18 Print Date 10/08/2024

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.