

5114 Epoxy Hardener

Version Number 1.0 Page 1 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

SAFETY DATA SHEET

5114 Epoxy Hardener

Section 1. Identification

GHS product identifier : 5114 Epoxy Hardener

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20051084Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation)

: CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

ACUTE TOXICITY (oral) - Category 3
EYE IRRITATION - Category 2A

GHS label elements



5114 Epoxy Hardener

Version Number 1.0 Page 2 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Hazard pictograms

Signal word : Danger

Hazard statements : Toxic if swallowed.

Causes serious eye irritation.

Precautionary statements

Not applicable.

Prevention: Wear eye or face protection. Do not eat, drink or smoke when using

this product. Wash thoroughly after handling.

Response : IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Rinse mouth. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements
Hazards not otherwise classified:

None known. None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Chemical name : Mixture Other means of identification : FO20051084

CAS number/other identifiers

Ingredient name	%	CAS number
Cyclohexanamine	>= 5 - < 10	108-91-8
3-Aminopropyldimethylamine	>= 5 - <= 10	109-55-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



5114 Epoxy Hardener

Version Number 1.0 Page 3 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur. Wash $\,$

clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician.

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation
Skin contact
No known significant effects or critical hazards.
No known significant effects or critical hazards.

Ingestion : Toxic if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation



5114 Epoxy Hardener

Version Number 1.0 Page 4 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media : In case of fire, use water spray (fog), foam, dry chemical or CO₂.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container may burst.

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without



5114 Epoxy Hardener

Version Number 1.0 Revision Date 10/28/2024

For emergency responders

Page 5 of 16 Print Date 10/29/2024

unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

suitable training. Evacuate surrounding areas. Keep unnecessary and

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach

> release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Do

not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be

hazardous. Do not reuse container.

Advice on general occupational

hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See



5114 Epoxy Hardener

Version Number 1.0 Revision Date 10/28/2024

Page 6 of 16 Print Date 10/29/2024

also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Cyclohexanamine	ACGIH TLV (1996-05-18) TWA 41 mg/m3 10 ppm NIOSH REL (1994-06-01) TWA 40 mg/m3 10 ppm OSHA PEL 1989 (1989-03-01) TWA 40 mg/m3 10 ppm
3-Aminopropyldimethylamine	None.

Appropriate engineering controls

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



5114 Epoxy Hardener

Version Number 1.0 Page 7 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color NO PIGMENT Odor Not available. Not available. **Odor threshold** Not available. **Melting point** Not available. **Boiling point** Not available. Not available. Flash point **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available.



5114 Epoxy Hardener

Version Number 1.0 Page 8 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

(flammable) limits Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not applicable.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7)

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Keep away from strong acids.

Oxidizer.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure
Cyclohexanamine				
	LD50 Oral	Rat	11 mg/kg	-
1,3-Propanediamine, N1,N1-di	methyl-			
	LD50 Oral	Rat	1,870 mg/kg	-

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

	Product/ingredient name	Result	Species	Score	Exposure	Observation
--	-------------------------	--------	---------	-------	----------	-------------



5114 Epoxy Hardener

Version Number 1.0 Page 9 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Cyclohexanamine	Eyes - Severe irritant	Rabbit	-	0.083 hrs	-
	Skin - Severe irritant	Human	-	48 hrs	-
	Skin - Severe irritant	Rabbit	-	24 hrs	-
	Skin - Severe irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-	24 hrs	-
1,3-Propanediamine, N1,N1-dimethyl-	Eyes - Moderate irritant	Rabbit	-		-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Cyclohexanamine	-	3	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary: Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.



5114 Epoxy Hardener

Version Number 1.0 Page 10 of 16
Revision Date 10/28/2024 Print Date 10/29/2024

Aspiration hazard

Not available.

Information on the likely routes of

Not available.

exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.

Ingestion : Toxic if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following: pain or irritation,

watering, redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.

Teratogenicity : Not available. **Developmental effects** : Not available.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates



5114 Epoxy Hardener

Version Number 1.0 Page 11 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
5114 Epoxy Hardener	123 mg/kg	N/A	N/A	N/A	N/A
Cyclohexanamine	11 mg/kg	N/A	N/A	N/A	N/A
1,3-Propanediamine, N1,N1-dimethyl-	1870 mg/kg	N/A	N/A	N/A	N/A

Other information: This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Cyclohexanamine			
	Acute LC50 0.47 Mg/l Fresh	Fish - Danio rerio	96 h
	water		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Cyclohexanamine	3.7	3.16	low
1,3-Propanediamine, N1,N1-	-0.352	-	low
dimethyl-			

Mobility in soil



5114 Epoxy Hardener

Version Number 1.0 Page 12 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR : UN2735, AMINES, LIQUID, CORROSIVE, N.O.S.(3-

Ground/Air/Water Aminopropyldimethylamine), 8, PG III

International Air : UN2735, AMINES, LIQUID, CORROSIVE, N.O.S.(3-

ICAO/IATA Aminopropyldimethylamine), 8, PG III

International Water : UN2735, AMINES, LIQUID, CORROSIVE, N.O.S.(3-

IMO/IMDG Aminopropyldimethylamine), 8, PG III

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed



5114 Epoxy Hardener

Version Number 1.0 Revision Date 10/28/2024

Page 13 of 16 Print Date 10/29/2024

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Not listed

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Listed Cyclohexanamine

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

Chemicals)

Not listed

Not listed

Not listed

Not listed

DEA List II Chemicals (Essential Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312



5114 Epoxy Hardener

Version Number 1.0 Page 14 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Classification : ACUTE TOXICITY - oral - Category 3

EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
Cyclohexanamine	>= 5 - < 10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
1,3-Propanediamine, N1,N1-dimethyl-	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 4 EYE IRRITATION - Category 2A

Not applicable.

State regulations

Massachusetts : The following components are listed:

Cyclohexanamine

3-Aminopropyldimethylamine

New York : The following components are listed:

Cyclohexanamine

New Jersey : The following components are listed:

Cyclohexanamine

3-Aminopropyldimethylamine

Pennsylvania : The following components are listed:

Cyclohexanamine

3-Aminopropyldimethylamine

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : Not determined.

International regulations

Inventory list

Australia: Not determined.Canada: Not determined.China: Not determined.



5114 Epoxy Hardener

Version Number 1.0 Page 15 of 16 Revision Date 10/28/2024 Print Date 10/29/2024

Eurasian Economic Union : **Russian Federation inventory:** Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand: Not determined.Philippines: Not determined.Republic of Korea: Not determined.Taiwan: Not determined.Thailand: Not determined.Turkey: Not determined.

United States : All components are active or exempted.

Viet Nam : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 10/29/2024Date of issue/Date of revision: 10/28/2024Date of previous issue: 10/25/2024

Version : 1.0

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.



5114 Epoxy Hardener

Version Number 1.0 Revision Date 10/28/2024 Page 16 of 16 Print Date 10/29/2024

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.